

**KRISBOW®**

# CONSTRUCTION



**SCAN**

FOR OUR LATEST VIDEO



**SCAN**

FOR BROCHURE & CATALOG



**SCAN**

FOR OUR STORE LOCATION

# COMPACTOR MACHINE

## RAMMER TAMPING



### Features :

- Specific Honda engine
- Germany rubber vibration
- Complete with transport wheel

### Standard Accessories:



Rammer transport wheel



Durable plastic oil tank

<b>Article No</b>	<b>10125306</b>
<b>Model No.</b>	<b>GPRT70</b>
<b>Description</b>	<b>Rammer Tamping 70 kg 13KN GXR120</b>
<b>Specification</b>	
<b>Engine Type</b>	Gasoline, Honda GXR120
<b>Engine</b>	Air-cooled, 4-cycle, single cylinder
<b>Power kW (hp)</b>	2.7 (3.6)
<b>Impact Force (kN)</b>	13
<b>Jumping Stroke (mm)</b>	40 - 80
<b>Shoe Size (mm)</b>	340 x 285
<b>Dimension (mm)</b>	345 x 705 x 1055
<b>Weight (kg)</b>	75

## COMPACTOR



### Features :

- Radius base plate for ways access to corners
- Sealed belt cover to prevent sand and oil in
- Complete with transport wheel

### Standard Accessories:



Compactor rubber mat



Compactor transport wheel

<b>Article No</b>	<b>10125307</b>
<b>Model No.</b>	<b>GPCF83</b>
<b>Description</b>	<b>Compactor 83 kg 13KN GX160</b>
<b>Specification</b>	
<b>Engine Type</b>	Gasoline, Honda GX160
<b>Engine</b>	Air-cooled, 4-cycle, single cylinder
<b>Power kW (hp)</b>	4.0 (5.5)
<b>Centrifugal Force (kN)</b>	13
<b>Compaction Depth (cm)</b>	30
<b>Efficiency (m<sup>2</sup>/hr)</b>	660
<b>Plate Size (mm)</b>	530 x 500
<b>Dimension (mm)</b>	1100 x 830 x 500
<b>Weight (kg)</b>	83

**COMPACTOR REV**



**Features :**

- Reversible with heavy duty throttle control
- Complete with extension plate
- Complete with transport wheel

**Standard Accessories:**



Compactor REV extension plate



Compactor REV transport wheel

<b>Article No</b>	<b>10125318</b>
<b>Model No.</b>	<b>GPCR150</b>
<b>Description</b>	<b>Compactor Rev 150 kg 30KN GX200</b>
<b>Specification</b>	
<b>Engine Type</b>	Gasoline, Honda GX200
<b>Engine</b>	Air-cooled, 4-cycle, single cylinder
<b>Power kW (hp)</b>	4.8 (6.5)
<b>Centrifugal Force (kN)</b>	30.5
<b>Travel Speed (cm/s)</b>	25
<b>Compaction Depth (cm)</b>	50
<b>Efficiency (m<sup>2</sup>/hr)</b>	570
<b>Plate Size (mm)</b>	730 x 370
<b>Plate Size with Extention (mm)</b>	730 x 500
<b>Dimension (mm)</b>	930 x 570 x 860
<b>Weight (kg)</b>	150

**ROLLER VIBRATOR SINGLE DRUM**



**Features :**

- Self cleaning scrapers and beveled drum edge eliminates marking on surface
- Compact design, easy reach control, comfort and simplified transport
- 15L Corrosion free water tank, easily removable for filling and cleaning

<b>Article No</b>	<b>10198739</b>
<b>Model No.</b>	<b>GPRV200</b>
<b>Description</b>	<b>Roller Vibrator Single Drum 200 kg</b>
<b>Specification</b>	
<b>Engine Type</b>	Gasoline, Honda GX160
<b>Engine</b>	Air-cooled, 4-cycle, single cylinder
<b>Power kW (hp)</b>	4.0 (5.5)
<b>Drum Diameter (mm)</b>	580 x ø400
<b>Water Tank Capacity L (Gal)</b>	15 (3.3)
<b>Centrifugal Force (kN)</b>	10
<b>Frequency vpm (Hz)</b>	4560 (76)
<b>Dimension (mm)</b>	1350 x 696 x 1320
<b>Travel Speed (km/h)</b>	0-1.5
<b>Gross Weight (kg)</b>	215
<b>Weight (kg)</b>	150



Deadman control and reversing protection



Variable height adjustment for operator's comforts



Narrow overhang for operation close to walls and curbs



Thick drum shells for longer drum life

**ROLLER VIBRATOR DOUBLE DRUM**



**Features :**

- Ergonomically designed handle level
- Mechanical parking break
- Side and curb clearance allow for the closest to approach wall and other obstacles

<b>Article No</b>	<b>10508746</b>
<b>Model No.</b>	<b>GPRVD650</b>
<b>Description</b>	<b>Roller Vibrator Double Drum 650kg</b>
<b>Specification</b>	
<b>Engine Type</b>	KUBOTA E75-NB3
<b>Engine</b>	Air-cooled, 4-cycle, single cylinder
<b>Power kW (hp)</b>	6.3 (8.4)
<b>Centrifugal Force (kN)</b>	11.3
<b>Drum Diameter (mm)</b>	650 x ø402
<b>Statistic Linear Force (N/cm)</b>	51
<b>Travel Speed (km/h)</b>	0-3.6
<b>Water Tank Capacity L (Gal)</b>	40 (8.8)
<b>Frequency vpm (Hz)</b>	3300 (55)
<b>Dimension (mm)</b>	2378 x 696 x 1130
<b>Weight (kg)</b>	670



**ASPHALT-CONCRETE CUTTER MACHINE**

**CUTTER ASPHALT-CONCRETE**



**Standard Accessories:**



Cutter Asphalt-Concrete 14"

**Features :**

- Super rigid box frame
- Ergonomically designed
- Large water tank

<b>Article No</b>	<b>10137515</b>
<b>Model No.</b>	<b>GPCTS144</b>
<b>Description</b>	<b>Cutter Asphalt-Concrete 12-16</b>
<b>Specification</b>	
<b>Engine Type</b>	Gasoline, Honda GX390
<b>Engine</b>	Air-cooled, 4-cycle, single cylinder
<b>Power kW (hp)</b>	9.6 (13)
<b>Max Cutting Depth (cm)</b>	14
<b>Blade Size (cm/Inch)</b>	30-40 / 12-16
<b>Deep adjustment</b>	Handle Rotation
<b>Driving</b>	Manual Push
<b>Water Tank Capacity (L)</b>	35
<b>Operation Mass (kg)</b>	144
<b>Dimension (mm)</b>	1550 x 600 x 950
<b>Weight (kg)</b>	176

**DIAMOND CUTT WHEEL 14"**



Article No	Model No.	Description	Dimension (mm)	Weight (kg)
10092870	GPDA14	Diamond Cutt Wheel 14" Asphalt	350 x 350 x 3	1.1
10092871	GPDC14	Diamond Cutt Wheel 14" Concrete	350 x 350 x 3	1.1




**SCREED FINISHING**

**Features :**

- Specially design, hardened aluminium blade
- Heavy duty rubber mounts to reduce the vibration on handle
- Adjustable handle position



The blade is easily changed within 2 minutes



Horizontal position

**SCREED BLADE**


<b>Article No</b>	<b>10125321</b>
<b>Model No.</b>	<b>GPSF12</b>
<b>Description</b>	<b>Screed Finishing 12 kg 1.8m GX35</b>
<b>Specification</b>	
<b>Engine Type</b>	Gasoline, Honda GX35
<b>Engine</b>	Air-cooled, 4-cycle, single cylinder
<b>Power kW (hp)</b>	1.2 (1.6)
<b>Blade Size (m)</b>	1.8
<b>Blade Weight (kg)</b>	4.36
<b>Engine Weight (kg)</b>	12.7
<b>Engine Dimension (mm)</b>	700 x 500 x 550

Article No	Model No.	Description	Dimension (mm)	Weight (kg)
10125324	GPSB12	Screed Blade 1.2m	1200 x 80 x 112	3.5
10125325	GPSB18	Screed Blade 1.8m	1800 x 80 x 112	5.3
10125326	GPSB30	Screed Blade 3m	3000 x 80 x 112	8.8

**TROWEL**

**Standard Accessories:**


Trowel lifting hook



Trowel transport wheel



Lifting tube

**Features :**

- Heavy weight design for superior finishing result
- Complete with lifting tube and transport wheel
- Screw control for blade adjustment

<b>Article No</b>	<b>10125319</b>
<b>Model No.</b>	<b>GPTR90</b>
<b>Description</b>	<b>Trowel 90gg R91cm GX160</b>
<b>Specification</b>	
<b>Engine Type</b>	Gasoline, Honda GX160
<b>Engine</b>	Air-cooled, 4-cycle, single cylinder
<b>Power kW (hp)</b>	4.0 (5.5)
<b>Rotor Diameter (cm)</b>	91
<b>Guard Diameter (cm)</b>	94
<b>Operation Mass (kg)</b>	90
<b>Engine Weight (kg)</b>	95
<b>Engine Dimension (mm)</b>	1000 x 1000 x 840

**POWER PACK HYDRAULIC**

**Features :**

- Power on demand
- Available to shift the hydraulic oil flow HP13/30-20L
- Oil level sight gauge

<b>Article No</b>	<b>10198731</b>
<b>Model No.</b>	<b>GPHPU</b>
<b>Description</b>	<b>Power Pack Hydraulic GX390 Hose 6m</b>
<b>Specification</b>	
<b>Engine Type</b>	Gasoline, Honda GX390
<b>Engine</b>	Air-cooled, 4-cycle, single cylinder
<b>Power kW (hp)</b>	9.6 (13)
<b>Flow (L / min)</b>	30 / 20
<b>Pressure (bar)</b>	138
<b>Weight (kg)</b>	90
<b>Dimension (mm)</b>	810 x 620 x 625

**JACK HAMMER BREAKER HYDRAULIC**

**Features :**

- High blow energy and frequency give high productivity
- Low vibration handle mechanism, reducing the risk of HAVS.
- Unique return blow action allows the operator to power the tool free

<b>Article No</b>	<b>10198735</b>
<b>Model No.</b>	<b>GPHPJH</b>
<b>Description</b>	<b>Jack Hammer Breaker Hydraulic Anti-Vib</b>
<b>Specification</b>	
<b>Blow Rate (bpm)</b>	1600
<b>Pressure (bar)</b>	98 - 138
<b>Steel Size (mm)</b>	25 x 108
<b>Flow (L / min)</b>	20
<b>Weight (kg)</b>	27
<b>Dimension (mm)</b>	700 x 200

**CIRCULAR SAW HYDRAULIC**

**Features :**

- Specially designed with chart permits to walk behind
- Cutting Blade for concrete, asphalt or metal
- Big volume water tank on chart with cooling dan dust reducing

<b>Article No</b>	<b>10198736</b>
<b>Model No.</b>	<b>GPHPSH</b>
<b>Description</b>	<b>Circular Saw Hydraulic Hand</b>
<b>Specification</b>	
<b>Speed (rpm)</b>	4500
<b>Flow (L / min)</b>	26 - 30
<b>Pressure (bar)</b>	105 - 145
<b>Blade Size mm (inch)</b>	356 (14")
<b>Weight (kg)</b>	12
<b>Dimension (mm)</b>	656 x 262

<b>Article No</b>	<b>Code</b>	<b>Description</b>
<b>10198738</b>	GPHPSC	Circular Saw Cart For Hydraulic Saw

**TRASH PUMP HYDRAULIC**

**Features :**

- Light weighted and compact design for easy transportation
- Pumping solids up to 100mm in diameter
- High-quality components such as polyurethane pump casing and impeller guarantee a longer service life

<b>Article No</b>	<b>10198737</b>
<b>Model No.</b>	<b>GPHPTP</b>
<b>Description</b>	<b>Trash Pump Hydraulic Portable Hose 10m</b>
<b>Specification</b>	
<b>Pressure (bar)</b>	105 - 140
<b>Flow (L / min)</b>	26 - 35
<b>Output (L / min)</b>	1700
<b>Outlet (mm)</b>	75
<b>Speed (rpm)</b>	3600
<b>Max Lift (m)</b>	30
<b>Weight (kg)</b>	14.5
<b>Dimension (mm)</b>	450 x 315

# CIVIL CONSTRUCTION MACHINE



## VIBRATOR ENGINE



Standard Accessories:



Vibrator Head 38mm

Features :

- High frequency vibration
- Quick change with Plug-in system vibrator coupling
- The low speed of both the vibrator and vibrator drive unit result in longer service life

<b>Article No</b>	<b>10125322</b>
<b>Model No.</b>	<b>GPV55</b>
<b>Description</b>	<b>Vibrator Engine 21 kg 5.5HP GX160</b>
<b>Specification</b>	
<b>Engine Type</b>	Gasoline, Honda GX160
<b>Engine</b>	Air-cooled, 4-cycle, single cylinder
<b>Power kW (hp)</b>	4.0 (5.5)
<b>Vibrator Head Dia x Length (mm)</b>	38 x 442
<b>Flexible Hose Length (m)</b>	6
<b>Casing &amp; Poker Weight (kg)</b>	12
<b>Revolution of Flexible Shaft (rpm)</b>	3000 - 3600
<b>Vibrator Amplitudo (mm)</b>	1.2
<b>Weight (kg)</b>	21
<b>Dimension (mm)</b>	540 x 420 x 430

## VIBRATOR ELECTRIC



Standard Accessories:



Vibrator Head 38mm

Features :

- Anti dust and liquid on-off button
- Quick change with Plug-in system vibrator coupling
- Light vibrator load

<b>Article No</b>	<b>10125323</b>
<b>Model No.</b>	<b>GPVE15</b>
<b>Description</b>	<b>Vibrator Electric PVE2 1.5Kw 230V 50HZ</b>
<b>Specification</b>	
<b>Power Input (kw)</b>	1.5
<b>Voltage (V)</b>	220
<b>Vibrator Head Dia x Length (mm)</b>	38 x 442
<b>Flexible Hose Length (m)</b>	6
<b>Casing &amp; Poker Weight (kg)</b>	12
<b>Revolution of Flexible Shaft (rpm)</b>	3000 - 3600
<b>Weight (kg)</b>	5.5
<b>Dimension (mm)</b>	385 x 420

## VIBRATOR HEAD PREMIUM



Article No	Code	Description	Dimension (mm)	Weight (kg)
10125327	GPVH38	Vibrator Head Premium D38-6M	6000 x ø38	12

# WATER PUMP

## WATER PUMP ENGINE



**Accessories Include:**

**Inlet Hose:**



Length (m) : 6

**Outlet Hose:**



Length (m) : 30

**Optional model :**



**Fixed Water Pump**



**Silent Water Pump**

**Features :**

- Suitable for outdoor work
- Convenient refueling system

Article No.	10497096	10497195	10497194
Model No.	BPPD800	BPPD500	BPPD400
Description	Water Pump Engine 800M3/H 10 inch	Water Pump Engine 500M3/H 8 inch	Water Pump Engine 400M3/H 6 inch
Specification			
Engine Type	FAW CA4DF2-12D	FAW 4DX23-90D	FAW 4DX21-53D
Power kW (hp)	84 (112)	57 (76)	39 (52)
Flow Rate (m3/h)	800	500	400
Head (m)	13	15	15
Inlet Size (inch)	10"	8"	6"
Outlet Size (inch)	10"	8"	6"
Suction Head (m)		7	
Dimension (mm)	2700 x 1000 x 1400		
Weight (kg)	1250	1050	950

**KRISBOW®**

*Distributed by:*