



# PACKAGING EQUIPMENT



**SCAN**  
FOR OUR LATEST VIDEO



**SCAN**  
FOR BROCHURE & CATALOG



**SCAN**  
FOR OUR STORE LOCATION

# STRAPPING

## PLASTIC STRAPPING TOOLS



KW0102982



- Features :
- Heavy duty used
  - Made from iron steel
  - Profesional and easy to use



KW0102983

Article No.	KW0102982	KW0102983	KW0104112
Model No.	PRPST0919	PRPSC16	PRPSC19
Description	Plastic Strapping Tensioner 9-19mm	Plastic Strapping Clamping Tool 16mm	Plastic Strapping Clamping Tool 19mm
<b>Specification</b>			
Function	Tightening	Clamping	
Strap Material	Plastic strap (PP, PET)		
Strap Width (mm)	9 – 19	16	19
Strap Thicness (mm)	0.4 – 1.0	0.6 – 0.8	
Dimension (mm)	267 x 71 x 135	505 x 122 x 45	550 x 125 x 45
Weight (kg)	1.33	1.85	2

## STEEL STRAPPING TOOLS



KW0101830



- Features :
- Heavy duty used
  - Made from iron steel
  - Profesional and easy to use



KW0102719

Article No.	KW0101830	KW0102719	KW0102720
Model No.	PRSSST0919	PRSSC16	PRSSC19
Description	Steel Strap Tensioner 9-19mm	Steel Strap Clamping Tool 16mm	Steel Strap Clamping Tool 19mm
<b>Specification</b>			
Function	Tightening	Clamping	
Strap Material	Steel strap		
Strap Width (mm)	9 – 19	16	19
Strap Thicness (mm)	0.4 – 1.0	0.6 – 0.8	
Dimension (mm)	267 x 71 x 135	505 x 122 x 45	550 x 125 x 45
Weight (kg)	1.33	1.85	2

## STRAPPING

### SEMI AUTO PLASTIC STRAPPING MACHINE



KW1500289



- Features :
- Eco power due to auto stop motor
  - Anti overheat element for less maintenance
  - Adjustable strapping tension force



KW1500290

Article No.	KW1500289		KW1500290	
Model No.	PRSTA4890		PRSTA7890	
Description	Strapping Table Auto 480mm		Strapping Table Auto 780mm	
<b>Specification</b>				
Power (W / V / Hz)	340 / 220 / 50			
Strap Material	Plastic strap (PP, PET )			
Strap Width (mm)	6 – 15			
Strap Thickness (mm)	0.8			
Strapping Tension Rate	40 – 480 N adjustable			
Working Table Height (mm)	480		780	
Working Table Area (mm)	900 x 580			
Dimension (mm)	1500 x 580 x 480		900 x 580 x 780	
Weight (kg)	90		100	

### AUTOMATIC PLASTIC STRAPPING MACHINE



**Features:**

- Aluminium rigid machine structure, durable for continuous operation
- Easy set-up loading with outside strapping roll dispenser
- Can be combined with other machine for automation system
- Adjustable strapping tension rate up to 600Nm
- Reliable PLC by Mitsubishi and Omron photoelectric switch
- Optimizing strapping speed up to 2 second per cycle

Article No.	10115840
Model No.	ASM-15
Description	Automatic Strapping Machine W80H60
<b>Specification</b>	
Power supply (Ph/VAC/Hz)	3 / 380 / 50-60
Power consumption (w)	400
Strap Material	Plastic strap (PP)
Strap Width (mm)	9, 12, 15
Strapping Tension (N)	40-600 adjustable
Strapping Speed (Sec/Strap )	2.18
Strap Type	Full Automatic A
Arch Size (mm)	800 × 600
Machine Size (mm)	1100 × 600 × 1540
Machine Weight (kg)	180



**STRAPPING**

**AUTO PALLET STRAPPING MACHINE**



Features :

- Portable pallet strapping, flexible, efficient and less maintenance
- Rapid speed : 0.2 sec/ cycle, 30 cycle/min
- Easy set-up loading with outside strapping roll dispenser and operation

<b>Article No.</b>	<b>10093522</b>
<b>Model No.</b>	<b>PRPS15</b>
<b>Description</b>	<b>Pallet Strapping Machine 15mm</b>
<b>Specification</b>	
<b>Power (W / V / Hz)</b>	340 / 220 / 50
<b>Strap Material</b>	Plastic strap (PP)
<b>Strap Width (mm)</b>	9 – 15
<b>Strapping Tension (N)</b>	100 – 600
<b>Strapping Speed (Sec/Strap )</b>	2
<b>Leg Chute Length (mm)</b>	1000
<b>Dimension (mm)</b>	1860 x 560 x 1500
<b>Weight (kg)</b>	180

**SEALER & VACUUM**



**PEDAL SEALER**



10115838

Features :

- Impulse sealing with adjustable heating control
- Economic power usage with safety fuse, electricity power only used during sealing
- Foot pedal operation, let your both hands free to hold the plastic bags to be sealed

<b>Article No.</b>	<b>10115727</b>	<b>10115838</b>
<b>Model No.</b>	<b>PRPS4505</b>	<b>PRSP6005</b>
<b>Description</b>	<b>Pedal Impulse Sealer 450mm</b>	<b>Pedal Impulse Sealer 600mm</b>
<b>Specification</b>		
<b>Power (W / V / Hz)</b>	800 / 220-240 / 50-60	1000 / 220-240 / 50-60
<b>Sealing Length (mm)</b>	450	600
<b>Sealing Width (mm)</b>	2-5	
<b>Dimension (mm)</b>	550 x 520 x 880	900 x 580 x 780
<b>Weight (kg)</b>	21	24.5

## SEALER & VACUUM

### PLASTIC SEALER



KW2001071

KW2001072

KW2001070

#### Features :

- Suitable for sealing all kind of PE, PP, combined plastic film and aluminium plastic film
- Simultaneously sealing and cutting

Article No.	KW2001071	KW2001072	KW2001070
Model No.	PRSC2002	PRSC3002	PRSC4002
Description	Sealer And Cutter Plastic 200mm	Sealer And Cutter Plastic 300mm	Sealer And Cutter Plastic 400mm
<b>Specification</b>			
Power (W / V / Hz)	300 / 220 / 50		
Sealing Length (mm)	200	300	400
Sealing Width (mm)	2		
Sealing Thickness (mm)	0.01 - 0.8		
Dimension (mm)	300 x 75 x 150	430 x 85 x 160	530 x 85 x 170
Weight (kg)	2.4	3.75	5.2

### VACUUM PACKAGING



Article No.	KW1500998
Model No.	PRMVP28
Description	Mini Vacuum Packager 280mm
<b>Specification</b>	
Power (W / V / Hz)	150 / 220 / 50
Vacuum (Mpa)	0.045
Sealing Length (mm)	40 - 280
Dimension (mm)	350 x 140 x 70
Weight (kg)	2.4

### THERMAL SHRINK PACKING MACHINE



#### Features :

- The machine adopts auto program control
- Vacuum time, gas flushing time, and sealing time are fully adjustable
- Adopt non-chamber mechanism with double gas nozzles.

Article No.	10115842
Model No.	PRTSP3516
Description	Thermal Shrink Packing Machine
<b>Specification</b>	
Power (V / Hz)	220 / 50
Heater Power (Kw)	6.5
Conveyor Speed (m/min)	0 - 15
Tunnel Size (mm)	1000 x 400 x 200
Product Size (mm)	350 x 160
Conveyor Loading Max (kg)	25
Tunnel Temperature Max (oC)	200
Shrink Film	POF, PVC, PP, PE
Dimension (mm)	1250 x 660 x 1320
Weight (kg)	90

# SEALER & VACUUM

## VACUUM PACKAGING



10112935



10089206

Features :

- For vacuum and sealing in one process
- Vacuum, hot sealing temperature and time can be adjusted easily
- Stable, reliable, good sealing strength, strong packing capacity, easy to use

Article No.	10112935	10089206
Model No.	PPVA3326	PPVA4034
Description	Vacuum Packager 330 x 260mm 1 Seal	Vacuum Packager 400 x 335mm 1 Seal
<b>Specification</b>		
Power (W / V / Hz)	400 / 220 / 50	900 / 220 / 50
Chamber Size (mm)	385 x 280 x 50	440 x 420 x 75
Sealing Bar Size (mm)	260 x 8	400 x 10
Sealing Bar Model)	Single	
Cycle Time (sec)	10-20	10 – 25
Capacity (m3/h)	10	20
Dimension (mm)	490 x 450 x 320	560 x 500 x 460

## VERTICAL VACUUM SEALER



Features :

- The machine adopts auto program control
- Vacuum time, gas flushing time, and sealing time are fully adjustable
- Adopt non-chamber mechanism with double gas nozzles.

Article No.	10118706
Model No.	PPSVV601I
Description	Sealer Vacuum Vertical 600mm
<b>Specification</b>	
Power (V / Hz)	220 / 50
Compressor Power (w)	550
Vacuum Pump Power (w)	900
Sealing Bar Size (mm)	600 x 8
Height for Vertical Packing (mm)	1060
Vacuum Stroke Volume (m/h)	20
Dimension (mm)	800 x 900 x 1700
Weight (kg)	240

## SEALER & VACUUM CONTINUOUS SEALER

**WITH PRINT**


10115724



10115725

**Features :**

- Adjustable heating and speed control
- Conveyor driven for continuous sealing with unlimited length
- Available with printing letters to print production or expired date (for 10115725)

Article No.	10115724	10115725
Model No.	PPCS0615	PPCSP0615
Description	Continuous Sealer 0.08 x 15-5kg	Continuous Sealer PR 0.08 x 15-5kg
<b>Specification</b>		
Operation	Horizontal	
Printing Letter	No Printing	30 letters ; 2 lines
Power (W / V / Hz)	500 / 220 / 50	600 / 220 / 50
Sealing Speed (m/min)	0 – 12	
Sealing Width (mm)	6 – 15	
Sealing Film Thickness (mm)	0.02 – 0.08	
Temperature Range (oC)	0 – 200	
Conveyor Capacity (kg)	5	
Dimension (mm)	900 x 480 x 380	950 x 480 x 380
Weight (kg)	35	45

## CARTON SEALER


**Features :**

- Top and bottom drive belts, ensure stable movement
- Adjustable tape overlength
- Infeed and outfeed roller working table
- Manual adjustable top squeezer
- Manual adjustable side guide rail

Article No.	10115839	
Model No.	PPCS5060	
Description	Sealer Vacuum Vertical 600mm	
<b>Specification</b>		
Power (W / V / Hz)	2 x 90 / 220 / 50	
Conveyor Speed (m/min)	20	
Rang of Box Dimensions (cm)	L	10 ~
	W	15 – 50
	H	12 – 60
Tape Width (mm)	36, 48, 60	
Height of Conveyor Table (cm)	55 – 80	
Dimension (mm)	163 x 80 x 133	
Weight (kg)	120	



# WRAPPING



## WRAPPING MACHINE



Features :

- OMRON PLC
- Turn table soft start/soft stop, heavy duty chain drive
- Variable carriage up/down speed

<b>Article No.</b>	<b>KW0500908</b>
<b>Model No.</b>	<b>PPPWM20</b>
<b>Description</b>	<b>Pallet Wrapping Machine 2T</b>
<b>Specification</b>	
<b>Power (kW / V / Hz)</b>	1.2 / 220 / 50
<b>Max. Load Size (mm)</b>	1200 x 1200 x 2400
<b>Turntable Diameter (mm)</b>	1650
<b>Turntable Height (mm)</b>	85
<b>Turntable Capacity (kg)</b>	2000
<b>Turntable Speed (rpm)</b>	3 - 12
<b>Packing Efficiency</b>	20 - 40 loads/h base on load
<b>Dimension (mm)</b>	2625 x 1650 x 2895
<b>Weight (kg)</b>	600



Features :

- HMI digital display
- Safety stop to avoid foot crush
- Turn table soft start/soft stop, heavy duty chain drive

<b>Article No.</b>	<b>10157241</b>
<b>Model No.</b>	<b>PPPWMGT20</b>
<b>Description</b>	<b>Pallet Wrapping Machine GT 2T</b>
<b>Specification</b>	
<b>Power (kW / V / Hz)</b>	1.5 / 220 / 50
<b>Max. Load Size (mm)</b>	1400 x 1400 x 2400
<b>Turntable Diameter (mm)</b>	2000
<b>Turntable Height (mm)</b>	78
<b>Turntable Capacity (kg)</b>	2000
<b>Turntable Speed (rpm)</b>	3 - 12
<b>Packing Efficiency</b>	20 - 40 loads/h base on load
<b>Dimension (mm)</b>	2745 x 2000 x 2860
<b>Weight (kg)</b>	650