

KRISBOW®

WELDING EQUIPMENT



SCAN

FOR OUR LATEST VIDEO



SCAN

FOR BROCHURE & CATALOG



SCAN

FOR OUR CHANNEL

MMA (SMAW) WELDING



MMA WELDING DC INVERTER



10621495



10621497



10621964

Features:

- Advanced IGBT technology
- Compact size, lightweight and modern welder
- Portable stick welding
- VRD (Voltage Reduction Device)



Standard Accessories :

Ground Clamp



Electrode Holder



Welding Mask



Hammer Brush



Glove



For 10211995

Article No.	10621495	10621497	10621964
Model No.	VRSD12	VRSD16	VRSD20
Description	MMA Welding 120A 1P	MMA Welding 160A 1P	MMA Welding 200A 1P
Spesification			
Rated Input Voltage (V/Ph/Hz)	220 / 1 / 50		
Rated Input Capacity (KVA)	7.2	7.2	9.2
Duty Cycle (%)	60%		
OCV (V)	24.8	26.4	28
Output Current Range (A)	10-120	10-160	10-200
Protection Class/Insulation Class	IP21S / F		
Dimension (mm)	300 x 130 x 235	300 x 150 x 235	
Weight (kg)	4.8	5.2	

MMA WELDING DC INVERTER



Features:

- IGBT full bridge technology
- Built in anti sticking, hot start and arc force adjustable
- Allow extension up to 100m connection cable



Standard Accessories :

Ground Clamp



Electrode Holder



Article No.	10058938	10058939
Model No.	VRSD40	VRSD50
Description	Inverter Dc Stick Welding 400A 3P	Inverter Dc Stick Welding 500A 3P
Spesification		
Rated Input Voltage (V/Ph/Hz)	380 / 3 / 50	380 / 3 / 50
Rated Input Capacity (KVA)	17.1	23.7
Duty Cycle (%)	60	60
OCV (V)	36	40
Output Current Range (A)	20-400	20-500
Protection Class/Insulation Class	IP21S / F	IP21S / F
Dimension (mm)	530 x 295 x 475	530 x 295 x 475
Weight (kg)	21	21

TIG (GTAW) WELDING



TIG WELDING DC



10449183

Features:

- TIG/MMA in one machine
- High frequency
- Microprocessor controlled for pulse

Standard Accessories :

Ground Clamp



Electrode Holder



Tig Torch



TIG WELDING AC/DC



10449184

Article No.	10449183	10449184
Model No.	VRT20	VRT31
Description	Tig Welding DC 200A 1P	Tig Welding AC/DC 315A 3P
Spesification		
Rated Input Voltage (V/Ph/Hz)	220 / 1 / 50	380 / 3 / 50
Rated Input Capacity (KVA)	6.1	8.9
Duty Cycle (%)	60%	60%
OCV (V)	85	60
Output Current Range (A)	TIG : 200	TIG : 315
	MMA : 200	MMA : 258
Protection Class/Insulation Class	IP21S / F	IP21S / F
Dimension (mm)	450 X 190 X 295	616 x 326 x 620
Weight (kg)	9.6	39

MIG-MAG (GMAW) WELDING

MIG-MAG WELDING



Features:

- MIG/TIG/MMA in one machine.
- Advanced IGBT inverter technology
- Ideal for gasless welding

Standard Accessories :

Mig Torch



Ground Clamp



Electrode Holder



Article No.	10449209
Model No.	VRM25
Description	Mig Welding 250A 1P with Trolley
Spesification	
Rated Input Voltage (V/Ph/Hz)	220 / 1 / 50
Duty Cycle (%)	60%
OCV (V)	58
Output Current Range (A)	MIG : 250
	TIG : 200
	MMA : 200
Wire Diameter (mm)	0.6-1.0
Protection Class/Insulation Class	IP21S / F
Dimension (mm)	610 x 300 x 658
Weight (kg)	39



Features:

- MIG/MMA in one machine.
- Advanced IGBT inverter technology
- Ideal for gasless welding
- Synergic mig control

Standard Accessories :

Mig Torch



Ground Clamp



Electrode Holder



Article No.	10449187	10449188
Model No.	VRMS35	VRMS50
Description	Mig Welding 350A 3P Synergic Trolley	Mig Welding 500A 3P Synergic Trolley
Spesification		
Rated Input Voltage (V/Ph/Hz)	380 / 3 / 50	
Duty Cycle (%)	60%	
OCV (V)	66	80
Output Current Range (A)	MIG : 350	MIG : 500
	MMA : 350	MMA : 500
Wire Diameter (mm)	0.8-1.2	1.0-1.6
Protection Class/Insulation Class	IP21S / F	
Dimension (mm)	616 x 326 x 620	
Weight (kg)	39	

PLASMA CUTTING



INVERTER PLASMA CUTTING



Features:

- Cutting speed increased 2 time comparing with oxy cutting
- Inverter Technology
- Ideal for cutting steel thickness max (25mm), stainless max (20mm), alluminium max (18mm)

Standard Accessories :

Plasma Torch



Ground Clamp



Article No.	10449182
Model No.	VRC4
Description	Plasma Cut 45A 1P
Spesification	
Rated Input Voltage (V/Ph/Hz)	220 / 1 / 50
Duty Cycle (%)	60%
OCV (V)	320
Output Current Cut (A)	45
Clean Cut/Severance Cut (mm)	20 / 28
Protection Class/Insulation Class	IP21S / F
Dimension (mm)	360 x 190 x 300
Weight (kg)	8



Features:

- Cutting speed increased 2 time comparing with oxy cutting
- Inverter Technology
- Ideal for cutting steel thickness max (45mm), stainless max (40mm), alluminium max (35mm)

Standard Accessories :

Plasma Torch



Ground Clamp



Article No.	10452853
Model No.	VRC10
Description	Plasma Cut 100A 3P
Spesification	
Rated Input Voltage (V/Ph/Hz)	380 / 3 / 50
Duty Cycle (%)	60%
OCV (V)	300
Output Current Cut (A)	100
Clean Cut/Severance Cut (mm)	40 / 45
Protection Class/Insulation Class	IP21S / F
Dimension (mm)	610 x 290 x 430
Weight (kg)	29

MULTIPROCESS WELDING



Features:

- MIG/TIG/MMA in one machine.
- Synergic mig control (automatically choose the suitable)
- Ideal for gasless welding

Standard Accessories :



Article No.	10449186
Model No.	VRMM16
Description	Mig-Tig Multi Welding Synergic 160A 1P
Spesification	
Rated Input Voltage (V/Ph/Hz)	220 / 1 / 50
Duty Cycle (%)	60%
OCV (V)	85
Output Current Range (A)	MIG : 160
	TIG : 160
	MMA : 140
Wire Diameter (mm)	0.6-1.0
Protection Class/Insulation Class	IP21S / F
Dimension (mm)	498 x 328 x 365
Weight (kg)	20



Features:


- CUT/TIG/MMA in one machine.
- Variable mode system
- Ideal for cutting steel thickness max (12mm), stainless max (10mm), aluminum max (8mm)

Standard Accessories :



Article No.	10449181
Model No.	VRCM4
Description	Plasma Cut-Tig Multi Welding 40A 1P
Spesification	
Rated Input Voltage (V/Ph/Hz)	220 / 1 / 50
Duty Cycle (%)	60%
OCV (V)	420
Output Current Range (A)	CUT : 40
	TIG : 160
	MMA : 160
Clean Cut/Severance Cut (mm)	6 / 12
Protection Class/Insulation Class	IP21S/F
Dimension (mm)	448 x 155 x 272
Weight (kg)	8

SPOT WELDING




Features:

- Available for welding of plate and wire of stainless, low carbon steel, low alloy steel, and non ferrous metal

Article No.	10471352	10471353
Model No.	VRSP10	VRSP25
Description	Spot Welding 380V 10KVA	Spot Welding 380V 25KVA
Spesification		
Rated Capacity (Kva)	10	10
Input Voltage (V/Ph)	380 / 3	380 / 3
No Load Voltage (V)	1,65 - 2,4	2.25 - 3.38
Adjustable Step Number	4	4
Duty Cycle	20%	20%
Welding Time Adjust (s)	0 - 9,99	0 - 9,99
Throat Depth (mm)	200	260
Welding Thickness (mm)	1,5 + 1,5	2.5 + 2.5
Dimension (mm)	730 x 320 x 930	900 x 440 x 1130
Weight (kg)	117	125

DENTPULL WELDING



Standard Accessories :

Steel Welding
Gun Set



Pulling Spot
Welding



Manually
Cupule



Screw Tool Box



Features:


- Digital control system offers greater stability of the output power
- Designed to repair different kinds of car steels such as conventional steel, stainless steel, etc

Article No.	10471239
Model No.	VRDPS12
Description	Dent Pull Welding Steel 12,3KVA
Spesification	
Rated Input Voltage (V/Ph/Hz)	220 / 1 / 50-60
Welding Current (A)	2000
Welding Time (S)	0 - 99
Welding Thickness (mm)	0.8 + 1.2
Dimension (mm)	420 x 720 x 890
Weight (kg)	23

ELECTRODE HOLDER and GROUND CLAMP



KW1400012, 10438378, KW1400771



KW1400014, KW1400015

Article No.	KW1400012	KW1400014	KW1400015	10438378	KW1400771
Model No.	VRPEH3	VRPGC3	VRPGC5	VRPEH5	VRPAEH8
Description	Electrode Holder 300A	Ground Clamp 300A	Ground Clamp 500A	Electrode Holder 500A	Electrode Holder 800A
Spesification					
Working (A)	300	300	500	500	800

CONSUMABLE

MIG-MAG (GMAW) WELDING



10495799



10493831



10493830



10495800



10493833



10493832

Article No.	Model No.	Description
10495799	VRGT16	Mig Gun Torch 160A Set
10493831	VRACT08	Contact Tip M6x25 0.8mm (10Ea)
10493830	VRAN16	Nozzle Mig16 (10Ea)

Article No.	Model No.	Description
10495800	VRGT25	Mig Gun Torch 250A Set
10493833	VRACT1	Contact Tip M6x9x25 1.0mm (10Ea)
10493832	VRAN25	Nozzle Mig25 (10Ea)



10495801



10493834



10493835



10493836

Article No.	Model No.	Description
10495801	VRGT35	Mig Gun Torch 350A Set
10493835	VRACT1	Contact Tip M6 1.0mm (10Ea) Mig35
10493834	VRAN35	Nozzle Mig35 (10Ea)
10493836	VRAD35	Diffuser Mig35



10495802



10493834



10493835



10493836

Article No.	Model No.	Description
10495802	VRGT50	Mig Gun Torch 500A Set
10493838	VRACT12	Contact Tip M6 1.2mm (10Ea)
10493837	VRAN50	Nozzle Mig50 (10Ea)
10493839	VRAD50	Diffuser Mig50

TIG (GTAW) WELDING



10495797




10495798

Article No.	Model No.	Description
10495797	VRTT26	Tig Torch Wp26 Set
10495798	VRTT18	Tig Torch Wp18 Water Cooling Set



10493827-829



10493823-824

Article No.	Model No.	Description
10493827	VRACN5	Ceramic Nozzle No.5 F/Tig (10Ea)
10493828	VRACN6	Ceramic Nozzle No.6 F/Tig (10Ea)
10493829	VRACN7	Ceramic Nozzle No.7 F/Tig (10Ea)
10493823	VRACB16	Collet Body Dia 1.6 F/Tig (10Ea)
10493824	VRACB24	Collet Body Dia 2.4 F/Tig (10Ea)

TIG (GTAW) WELDING


10493825



10493826



10493821



10493822

Article No.	Model No.	Description
10493825	VRAC16	Collet Dia 1.6 F/Tig (10Ea)
10493826	VRAC24	Collet Dia 2.4 F/Tig (10Ea)

Article No.	Model No.	Description
10493821	VRALC	Long Back Cap F/Tig (2Ea)
10493822	VRASC	Short Back Cap F/Tig (2Ea)

PLASMA CUTTING


10495794



10493879



10493882



10493881



10493880

Article No.	Model No.	Description
10495794	VRP T4	Plasma Torch 40A Sg55 Set
10522586	VRAT4	Torch Head Sg55 F/ VRAT4
10493882	VRAS4	Shield Cup F/ VRCM4 (10Ea)
10493881	VRAN4	Nozzle 1.0mm F/ VRCM4 (10Ea)
10493880	VRAE4	Electrode F/ VRCM4 (10Ea)



10495795



10493881



10493884



10493885



10493886

Article No.	Model No.	Description
10495795	VRPT45	Plasma Torch 45A Ipt45 Set
10493881	VRANC45	Shield Cup F/ VRC4 (5Ea)
10493884	VRAN45	Nozzle F/ VRC4 (10Ea)
10493885	VRAD45	Diffuser F/ VRC4 (10Ea)
10493886	VRAE45	Electrode F/ VRC4 (10Ea)



10495796



10493889




10493887



10493888

Article No.	Model No.	Description
10495796	VRPT10	Plasma Torch 100A Wsd Set
10493889	VRAS10	Shield Cup F/ VRC10 (10Ea)
10493887	VRAN10	Nozzle F/ VRC10 (10Ea)
10493888	VRAE10	Electrode F/ VRC10 (10Ea)

GAS CUTTING



Standard Accessories :




Spare Rail 17 cm x 1.8m (KW1400075)

Features:

- Main body made of high strnght aluminum
- Advanced motor with fan for cooling
- Groove range I.Y.V (45)

Article No.	KW1400153
Model No.	VPCGRB15
Description	Gas Cutting With Rail Beetle
Spesification	
Rated Input Voltage (V/Ph/Hz)	220 / 1 / 50
Cutting Thickness (mm)	6-100
Cutting Speed (mm/min)	150- 800
Circle Cutting (mm)	290-540
Dimension (mm)	350 x 140 x 170
Weight (kg)	10



Standard Accessories :



Spare Rail 17 cm x 1.8m (KW1400075)

Features:

- Main body made of high strnght aluminum
- Advanced motor with fan for cooling
- Groove range I.Y.V (45)

Article No.	KW1400154
Model No.	VPCGRM15
Description	Gas Cutting With Rail Max
Spesification	
Rated Input Voltage (V/Ph/Hz)	220 / 1 / 50
Cutting Thickness (mm)	6-100
Cutting Speed (mm/min)	150- 800
Circle Cutting (mm)	390-640
Dimension (mm)	600 x 170 x 220
Weight (kg)	15



Features :

- Main body made of high strenght aluminum
- Advanced motor with fan for cooling
- Groove range I.Y.V (45)

Article No.	KW1400159
Model No.	VPCGP50
Description	Gas Cutting Profiling
Spesification	
Rated Input Voltage (V/Ph/Hz)	220 / 1 / 50
Cutting Thickness (mm)	6-100
Cutting Speed (mm/min)	50-750
Circle Cutting (mm)	20-600
Pipe Cutting (mm)	-
length of Line Cutting (mm)	1200
Max Size of Cutting Square / Rectangle	500 x 500 / 400 x 900
Dimension (mm)	750 x 300 x700
Weight (kg)	56

CUTTING TIP



For Acetylene



For LPG

Article No.	Description	Cutting Thickness (mm)	Cutting Speed (mm/min)
CH0000101	A3800 Cutting Tip Strong 25 ACT No.0	5 - 10	660 - 550
CH0000102	A3800 Cutting Tip Strong 25 ACT No.1	10 - 20	550 - 490
CH0000103	A3800 Cutting Tip Strong 25 ACT No.2	15 - 30	490 - 400
CH0000104	A3800 Cutting Tip Strong 25 ACT No.3	25 - 50	400 - 350
CH0000105	A3800 Cutting Tip Strong 25 ACT No.4	40 - 80	350 - 320
CH0000106	A3800 Cutting Tip Strong 25 ACT No.5	60 - 150	320 - 200
CH0000107	A3800 Cutting Tip Strong 25 ACT No.6	120 - 200	200 - 150
CH0000108	A3800 Cutting Tip Strong 25 ACT No.7	150 - 250	150 - 80
CH0000137	P3500 Cutting Tip Strong 25 LPG No.0	5 - 10	660 - 550
CH0000138	P3500 Cutting Tip Strong 25 LPG No.1	10 - 20	550 - 490
CH0000139	P3500 Cutting Tip Strong 25 LPG No.2	15 - 30	490 - 400
CH0000140	P3500 Cutting Tip Strong 25 LPG No.3	25 - 50	400 - 350
CH0000141	P3500 Cutting Tip Strong 25 LPG No.4	40 - 80	350 - 320
CH0000142	P3500 Cutting Tip Strong 25 LPG No.5	60 - 150	320 - 200
CH0000143	P3500 Cutting Tip Strong 25 LPG No.6	120 - 200	200 - 150
CH0000144	P3500 Cutting Tip Strong 25 LPG No.7	150 - 250	150 - 80

DRYER ELECTRODE

WELDING DRYER ROD



KW1401062

Features (KW1401062, KW1401063) :

- Knob adjustment temperature
- Low heat loss, high heat efficiency
- Display temperature control (5kg)



KW1401063

Article No.	KW1401062	KW1401063
Model No.	VPPADR5	VPPADR10
Description	Dryer Electrode 5Kg 220V AC	Dryer Electrode 10Kg 220V AC
Spesification		
Rated Input Voltage (V/Ph/Hz)	220 / 1 / 50	
Electrode Length (mm)	450	
Capacity (kg)	5	10
Max. Temperature °C	200	
Dimension (mm)	190 x 190 x 660	230 x 230 x 630
Weight (kg)	3	6

OVEN ELECTRODE

**Features:**

- Infrared radiation for heating
- Low heat loss, high heat efficiency
- Phase, variable, overheat, overpressure, alarm indicator

Article No.	KW1401064
Model No.	VPPAE06
Description	Dryer Electrode Oven Infra 60Kg
Spesification	
Rated Input Voltage (V/Ph/Hz)	220 / 1 / 50
Rated Input Capacity (kVA)	3,8
Electrode Length (mm)	450
Capacity (kg)	60
Max. Temperature ©	500
Dimension (mm)	570 x 720 x 1340
Weight (kg)	140

**Features:**

- Infrared radiation for heating
- Low heat loss, high heat efficiency
- Phase, variable, overheat, overpressure, alarm indicator

Article No.	KW1401065
Model No.	VPPAE10
Description	Dryer Electrode Oven Infra 100Kg
Spesification	
Rated Input Voltage (V/Ph/Hz)	380 / 3 / 50
Rated Input Capacity (kVA)	7,3
Electrode Length (mm)	450
Capacity (kg)	100
Max. Temperature ©	500
Dimension (mm)	1050 x 720 x 1250
Weight (kg)	225

KRISBOW®*Distributed by:*