07



CONSTRUCTION



COMPACTOR MACHINE

RAMMER TAMPING



- Features:
 Specific Honda engine
- Germany rubber vibration Complete with transport wheel

Standard Accessories:





Rammer transport wheel

Durable plastic oil tank

Article No	10125306
Model No.	GPRT70
Description	Rammer Tamping 70 kg 13KN GXR120
Specification	
Engine Type	Gasoline, Honda GXR120
Engine	Air-cooled, 4-cycle, single cylinder
Power kW (hp)	2.7 (3.6)
Impact Force (kN)	13
Jumping Stroke (mm)	40 - 80
Shoe Size (mm)	340 x 285
Dimension (mm)	345 x 705 x 1055
Weight (kg)	75

COMPACTOR



Features:

- Radius base plate for ways access to corners
- · Sealed belt cover to prevent sand and oil in
- · Complete with transport wheel

Standard Accessories:





Compactor rubber mat

Compactor transport wheel

Article No	10125307
Model No.	GPCF83
Description	Compactor 83 kg 13KN GX160
Specification	
Engine Type	Gasoline, Honda GX160
Engine	Air-cooled, 4-cycle, single cylinder
Power kW (hp)	4.0 (5.5)
Centrifugal Force (kN)	13
Compaction Depth (cm)	30
Efficiency (m²/hr)	660
Plate Size (mm)	530 x 500
Dimension (mm)	1100 x 830 x 500
Weight (kg)	83







- Reversible with heavy duty throttle control
- · Complete with extension plate
- · Complete with transport wheel

Standard Accessories:





Compactor REV extension plate

Compactor REV transport wheel

Article No	10125318
Model No.	GPCR150
Description	Compactor Rev 150 kg 30KN GX200
Specification	
Engine Type	Gasoline, Honda GX200
Engine	Air-cooled, 4-cycle, single cylinder
Power kW (hp)	4.8 (6.5)
Centrifugal Force (kN)	30.5
Travel Speed (cm/s)	25
Compaction Depth (cm)	50
Efficiency (m²/hr)	570
Plate Size (mm)	730 x 370
Plate Size with Extention (mm)	730 x 500
Dimension (mm)	930 x 570 x 860
Weight (kg)	150

ROLLER VIBRATOR SINGLE DRUM





Deadman control and reversing protection



Variable height adjusment for operator's comforts

- · Self cleaning scrapers and beveled drum edge eliminates marking on
- Compact design, easy reach control, comfort and simplified transport
 15L Corrosion free water tank, easily removable for filling and cleaning

Article No	10198739
Model No.	GPRV200
Description	Roller Vibrator Single Drum 200 kg
Specification	
Engine Type	Gasoline, Honda GX160
Engine	Air-cooled, 4-cycle, single cylinder
Power kW (hp)	4.0 (5.5)
Drum Diameter (mm)	580 x ø400
Water Tank Capacity L (Gal)	15 (3.3)
Centrifugal Force (kN)	10
Frequency vpm (Hz)	4560 (76)
Dimension (mm)	1350 x 696 x 1320
Travel Speed (km/h)	0-1.5
Gross Weight (kg)	215
Weight (kg)	150



Narrow overhang for operation close to walls and curbs



Thick drum shells for longer drum life



ROLLER VIBRATOR DOUBLE DRUM



Features:

- Ergonomically designed handle level
- · Mechanical parking break
- Side and curb clearance allow for the closest to approach wall and other obstacles

10508746
GPRVD650
Roller Vibrator Double Drum 650kg
KUBOTA E75-NB3
Air-cooled, 4-cycle, single cylinder
6.3 (8.4)
11.3
650 x ø402
51
0-3.6
40 (8.8)
3300 (55)
2378 x 696 x 1130
670

ASPHALT-CONCRETE CUTTER MACHINE

CUTTER ASPHALT-CONCRETE



- Super rigid box frameErgonomically designed
- Large water tank

Standard Accessories:



Cutter Asphalt-Concrete 14"

Article No	10137515
Model No.	GPCTS144
Description	Cutter Asphalt-Concrete 12-16
Specification	
Engine Type	Gasoline, Honda GX390
Engine	Air-cooled, 4-cycle, single cylinder
Power kW (hp)	9.6 (13)
Max Cutting Depth (cm)	14
Blade Size (cm/Inch)	30-40 / 12-16
Deep adjusment	Handle Rotation
Driving	Manual Push
Water Tank Capacity (L)	35
Operation Mass (kg)	144
Dimension (mm)	1550 x 600 x 950
Weight (kg)	176



Article No	Model No.	Description	Dimension (mm)	Weight (kg)
10092870	GPDA14	Diamond Cutt Wheel 14" Asphalt	350 x 350 x 3	1.1
10092871	GPDC14	Diamond Cutt Wheel 14" Concrete 350 x 350		1.1



SCREED FINISHING




SCREED BLADE



Features:

- · Specially design, hardened alumunium blade
- Heavy duty rubber mounts to reduce the vibration on handle
- · Adjustable handle position







Horizontal position

Article No	10125321
Model No.	GPSF12
Description	Screed Finishing 12 kg 1.8m GX35
Specification	
Engine Type	Gasoline, Honda GX35
Engine	Air-cooled, 4-cycle, single cylinder
Power kW (hp)	1.2 (1.6)
Blade Size (m)	1.8
Blade Weight (kg)	4.36
Engine Weight (kg)	12.7
Engine Dimension (mm)	700 x 500 x 550

Article No	Model No.	Description	Dimension (mm)	Weight (kg)
10125324	GPSB12	Screed Blade 1.2m	1200 x 80 x 112	3.5
10125325	GPSB18	Screed Blade 1.8m	1800 x 80 x 112	5.3
10125326	GPSB30	Screed Blade 3m	3000 x 80 x 112	8.8

TROWEL



Features:

- Heavy weight design for superior finishing result
- Complete with lifting tube and transport wheel
 Screw control for blade adjustment

	· ·
Article No	10125319
Model No.	GPTR90
Description	Trowel 90gg R91cm GX160
Specification	
Engine Type	Gasoline, Honda GX160
Engine	Air-cooled, 4-cycle, single cylinder
Power kW (hp)	4.0 (5.5)
Rotor Diameter (cm)	91
Guard Diameter (cm)	94
Operation Mass (kg)	90
Engine Weight (kg)	95
Engine Dimension (mm)	1000 x 1000 x 840

POWER PACK HYDRAULIC



- Power on demand
- Available to shift the hydraullic oil flow HP13/30-20L
- · Oil level sight gauge

Article No	10198731
Model No.	GPHPU
Description	Power Pack Hydraulic GX390 Hose 6m
Specification	
Engine Type	Gasoline, Honda GX390
Engine	Air-cooled, 4-cycle, single cylinder
Power kW (hp)	9.6 (13)
Flow (L / min)	30 / 20
Pressure (bar)	138
Weight (kg)	90
Dimension (mm)	810 x 620 x 625



JACK HAMMER BREAKER HYDRAULIC



Features:

- High blow energy and frequency give high productivity
 Low vibration handle mechanism, reducing the risk of HAVS.
 Unique return blow action allows the operator to power the tool free

Article No	10198735
Model No.	СРНРЈН
Model No.	СРПРЈП
Description	Jack Hammer Breaker Hydraulic Anti-Vib
Specification	
Blow Rate (bpm)	1600
Pressure (bar)	98 - 138
Steel Size (mm)	25 x 108
Flow (L / min)	20
Weight (kg)	27
Dimension (mm)	700 x 200

CIRCULAR SAW HYDRAULIC



Features:

- Specially designed with chart permits to walk behind
 Cutting Blade for concrete, asphalt or metal
- · Big volume water tank on chart with cooling dan dust reducing

Article No	10198736
Model No.	GPHPSH
Description	Circular Saw Hydraulic Hand
Specification	
Speed (rpm)	4500
Flow (L / min)	26 - 30
Pressure (bar)	105 - 145
Blade Size mm (inch)	356 (14")
Weight (kg)	12
Dimension (mm)	656 x 262

Article No	Code	Description
10198738	GPHPSC	Circular Saw Cart For Hydraulic Saw

TRASH PUMP HYDRAULIC



- Light weighted and compact design for easy transportation
 Pumping solids up to 100mm in diameter
- · High-quality components such as polyurethane pump casing and impeller guarantee a longer service life

Article No	10198737
Model No.	СРНРТР
Description	Trash Pump Hydraulic Portable Hose 10m
Specification	
Pressure (bar)	105 - 140
Flow (L / min)	26 - 35
Output (L / min)	1700
Outlet (mm)	75
Speed (rpm)	3600
Max Lift (m)	30
Weight (kg)	14.5
Dimension (mm)	450 x 315



CIVIL CONSTRUCTION MACHINE

VIBRATOR ENGINE



Features:

- · High frequency vibration
- · Quick change with Plug-in system vibrator coupling
- The low speed of both the vibrator and vibrator drive unit result in longer service life

Article No	10125322	
Model No.	GPV55	
Description	Vibrator Engine 21 kg 5.5HP GX160	
Specification		
Engine Type	Gasoline, Honda GX160	
Engine	Air-cooled, 4-cycle, single cylinder	
Power kW (hp)	4.0 (5.5)	
Vibrator Head Dia x Length (mm)	38 x 442	
Flexible Hose Length (m)	6	
Casing & Poker Weight (kg)	12	
Revolution of Flexible Shaft (rpm)	3000 - 3600	
Vibrator Amplitudo (mm)	1.2	
Weight (kg)	21	
Dimension (mm)	540 x 420 x 430	

VIBRATOR ELECTRIC



Features

- · Anti dust and liquid on-off button
- · Quick change with Plug-in system vibrator coupling
- Light vibrator load

Article No	10125323	
Model No.	GPVE15	
Description	Vibrator Electric PVE2 1.5Kw 230V 50HZ	
Specification		
Power Input (kw)	1.5	
Voltage (V)	220	
Vibrator Head Dia x Length (mm)	38 x 442	
Flexible Hose Length (m)	6	
Casing & Poker Weight (kg)	12	
Revolution of Flexible Shaft (rpm)	3000 - 3600	
Weight (kg)	5.5	
Dimension (mm)	385 x 420	

VIBRATOR HEAD PREMIUM



Article No Code		Code	Description	Dimension (mm)	Weight (kg)
10	0125327	GPVH38	Vibrator Head Premium D38-6M	6000 x ø38	12





WATER PUMP ENGINE



Accessories Include:

Inlet Hose:



Length (m):6

Outlet Hose:



Length (m):30

Optional model:



Fixed Water Pump



Silent Water Pump

- Suitable for outdoor work
- Convenient refueling system

Article No.	10497096	10497195	10497194
Model No.	BPPD800	BPPD500	BPPD400
Description	Water Pump Engine 800M3/H 10 inch	Water Pump Engine 500M3/H 8 inch	Water Pump Engine 400M3/H 6 inch
Specification			
Engine Type	FAW CA4DF2-12D	FAW 4DX23-90D	FAW 4DX21-53D
Power kW (hp)	84 (112)	57 (76)	39(52)
Flow Rate (m3/h)	800	500	400
Head (m)	13	15	15
Inlet Size (inch)	10"	8"	6"
Outlet Size (inch)	10"	8"	6"
Suction Head (m)	7		
Dimension (mm)	2700 x 1000 x 1400		
Weight (kg)	1250	1050	950



